Page 1 of 7



2020+ Kawasaki KRX 1000 Pull Plate # \$3237



TOOT

INSTALLATION INSTRUCTIONS Kawasaki KRX 1000 Pull Plate



PARTS LIST

PART #	DESCRIPTION	QTY
S3237	Pull Plate	1
MCS1280Z	M12x80 Bolt	2
MFW12Z	M12 Flat Washer	4
MLN12-1.75	M12 Nylock Nut	2

Tools Needed:

- Jack
- Jack Stands
- Ratchet or Impact (1/2" Drive)
- Wrenches (19mm, 17mm)
- Sockets (19mm, 17mm)

Disassembly:

- 1.) Place KRX in park (P) on a flat level surface. Engage parking brake. (Pro Tip : For extra safety, chock front tires to prevent KRX from rolling forward.)
- 2.) Elevate rear of machine until tires are off the ground.
- 3.) Place jack stands under frame, in suitable locations, for safety.
- 4.) Remove (4) M12 (17mm head) bolts from the rear radius rods. (See Images 1, 2, 3)

Assembly:

5.) Prepare Pull Plate and hardware that will be used. (See Image 4)

6.) Install stock upper bolts, through Pull Plate and into frame. Hand tighten only. (Note : This will require aligning the upper radius rod with the frame holes you're using. An assistant may be helpful.) 7.) Install supplied lower hardware, through Pull Plate and into frame. Hand tighten only. (Note : This will require aligning the lower radius rods with the frame holes you're using. An assistant may be helpful.) (See Image 5)

- 8.) Final tighten hardware, using red threadlocker.
- 9.) Reinstall wheels/tires, and place KRX back onto flat ground.
- 10.) Test drive and recheck all hardware/fasteners.

Thank you for choosing S3 Power Sports! Let us know if you have any questions! 855-221-7097







<u>Image 2</u>













